


K-Series Depth Filter Sheets

In the chemical industry it is necessary to filter out residues from raw-, intermediate- or finished products. Lacquers, colors, synthetic resins, pesticides, polymers, waxes as well as technical oils offer a broad spectrum for the effective employment of Pall depth filter. With 13 different retention rates the K series represents the standard depth filter sheet series from Pall, formerly SeitzSchenk.


The EKS, the EK 1 and the EK are used for fine particles. Grades K 100 through to K 900 cover the entire range from fine filtration through clarifying filtration to coarse filtration.




Material components

Due to their material composition and their structural design SeitzSchenk depth filters can basically be compared with a maze-like, extremely fine three-dimensional sieve with innumerous, branched micro"channels".

The main components are cellulose, diatomaceous earth and/or perlite and synthetic polymers. The cellulose generates the matrix of the depth filter. The diatomaceous earth and/or perlite are responsible for the clarifying effect. The synthetic polymers build up the wet strength and the the positive ZETA potential.





 $\Delta p = 100 \text{ kPa} (1 \text{ bar}), T = 20^{\circ}\text{C}, \text{ medium H}_2\text{O}$

Filtration. Separation. Solution.sm

Characterization

The tests are carried out according to the methods of the Technical/ Analytical Work Group within the European Depth Filtration Association or in accordance with in-house test methods.

Technical Data

| Sheet | Mass per unit area [g m-²] | Thickness [mm] | Ash [%] | Extractable ions soluble in acetic acid (5%) [mg m-²] | | |
|-------|-------------------------------|-------------------|------------|--|----|-----|
| | | | | Ca | Fe | Al |
| EKS | 1400 | 3.7 | 58 | 1800 | 15 | 150 |
| EKS1 | 1400 | 3.7 | 51 | 1800 | 15 | 140 |
| EK | 1350 | 3.7 | 46 | 1400 | 10 | 120 |
| KS 50 | 1350 | 3.7 | 46 | 1400 | 10 | 120 |
| KS 80 | 1350 | 3.7 | 46 | 1200 | 15 | 120 |
| K 100 | 1350 | 3.7 | 46 | 1400 | 15 | 120 |
| K 150 | 1350 | 3.9 | 46 | 1300 | 15 | 120 |
| K 200 | 1350 | 3.9 | 46 | 1200 | 15 | 110 |
| K 250 | 1300 | 4.0 | 46 | 1000 | 15 | 70 |
| K 300 | 1300 | 4.2 | 46 | 900 | 15 | 50 |
| K 700 | 1300 | 4.1 | 46 | 900 | 15 | 50 |
| K 800 | 1300 | 4.1 | 46 | 900 | 15 | 45 |
| K 900 | 1300 | 4.3 | 46 | 900 | 25 | 40 |

Heavy metals < 50 ppm (according to the Recommendation XXXVI/1 BgVV- German Federal Institute for Health Protection of Consumers and Veterinary Medicine).

Application

| | Sheet | Typical Application |
|--|---|---|
| | EKS EKS 1 EK KS 50 KS 80 | Fine clarification |
| | K 100 K 150 K 200 K 250 K 300 | Clarifying filtration Retention of activated carbon Retention of salts Removal of gels from silicones, alkyd resins, polymers Catalyst retention from various solutions |
| | K 700 K 800 K 900 | Retention of gels from resins (alkyd resins, polyacrylates) Silicon oils and silicon resins Tensides (clarifying filtration) |

The figures quoted in the diagrams and tables should be regarded as guidelines.

The following certificates are available:

- Technical Data sheet
- Certificate of Compliance with the Order according to DIN 50049-2.1/EN 10204-2.1
- EU Safety Data Sheet

The depth filters conform to the Recommendation XXXVI/1 BgVV (German Federal Institute for Health Protection of Consumers and Veterinary Medicine) and meet the requirements of the Lebensmittel- und Bedarfsgegenständegesetz - LMBG - (Foodstuff and other Commodities Act), in particular §§ 5, 30 and 31; they can be used for cold filtration of foodstuff without any reservation.

Important Note :

All information contained in this leaflet is based on today's 'State of the Art' knowledge. It does not claim to be complete, therefore no liability can be accepted. All users are advised to test our products to ensure they meet their specific requirements and to exercise all necessary care when in use. The information in the instruction manuals issued by us should be strictly observed. Departure from our specific instructions means we cannot accept any responsibility for damage which may result. Should you encounter specific problems, please contact our specialists. We reserve the right to make alterations without prior notice.



Fuels and Chemicals

Pall GmbH Planiger Strasse 137

55543 Bad Kreuznach/Germany

+49.(0)671.88220 phone +49.(0)671.8822200 fax

fuels.chemicals.de@pall.com email

Visit us on the Web at www.pall.com

Pall Corporation has offices and plants throughout the world in locations including: Argentina, Australia, Austria, Belgium, Brazil, Canada, China, France, Germany, India, Indonesia, Ireland, Italy, Japan, Korea, Malaysia, Mexico, the Netherlands, New Zealand, Norway, Poland, Puerto Rico, Russia, Singapore, South Africa, Spain, Sweden, Switzerland, Taiwan, Thailand, United Kingdom, United States, and Venezuela. Distributors are located in all major industrial areas of the world.

© Copyright 2006, Pall Corporation. Pall and (PALL), are trademarks of Pall Corporation. ® Indicates a Pall trademark registered in the USA. *Filtration. Separation. Solution.suis* a service mark of Pall Corporation.

Reorder Code. PFC-P107 engl. 1 04/06 PP

Filtration. Separation. Solution.sm