

Ultipleat® High Flow Series Filter Cartridges

Description

The Ultipleat® High Flow filter is a large-diameter, coreless, single open-ended, pleated cartridge with an inside-to-outside flow pattern.

The filter's unique crescent-shaped pleat geometry, combined with its large 152.4 mm (6-inch) diameter and proprietary range of available Pall filter media, allows you to use significantly fewer filters and smaller housings for high flow-rate applications.

Features and Benefits

- Coreless large diameter cartridge, synthetic construction, to minimize waste disposal
- High flow rate per filter cartridge
 - ◆ Up to 40 times fewer cartridges to change out
 - ◆ Up to 50% smaller filter system possible
- Available in a variety of filter lengths and grades
- Absolute-rated filter medium for reproducible performance
- Features proprietary unique crescent-shaped pleat geometry
- Inside-to-outside flow pattern that traps contaminant inside the element, thus preventing polluting the treated water during the cartridge change-out
- Handle for easy cartridge replacement



Materials of Construction

Filter Medium Type	Filter Medium	Support/Drainage Materials	End Caps	Wrap Materials
HDC® II Medium	High-Area Polypropylene Structure	Polypropylene	Glass-Filled Polypropylene	Polypropylene and Polyolefin Hotmelt
Profile® Medium in Ultipleat Format	Pleated Polypropylene Depth Structure	Polypropylene	Glass-Filled Polypropylene	Polypropylene
Ultipor® GF Medium	Resin Bonded Glass Fiber / Polyester Support	Polyester / Nylon	Glass-Filled Acetal	Polyester and Polyamide Hotmelt
Ultipleat CAS Medium	Pleated Polypropylene / Polyether Sulfone Membrane	Polypropylene	Glass-Filled Polypropylene	Polypropylene

Operating Conditions¹

	Polypropylene Medium/ CAS Composite Medium	Glass Fiber Medium
Maximum Differential Pressure ² (normal inside-to-outside flow)	3.44 bard at 82°C 50 psid at 180°F	3.44 bard at 121°C 50 psid at 250°F

1) Maximum temperature in aqueous systems is 60°C / 140°F for GF medium.

2) For fluids compatible with the filter element at the stated temperature.

Ordering Information/Specifications

Filter Cartridge Part Number: HFU ▲ ● ◆

Code ▲	Filter Dimensions, (nominal) Diameter (in / mm) x Length (in / mm)	Suggested Maximum Water Flow Per Cartridge- US gpm / L/min / MGD
620	6 / 152.4 x 20 / 508	175 / 663 / 0.25
640	6 / 152.4 x 40 / 1016	350 / 1325 / 0.5
660	6 / 152.4 x 60 / 1524	500 / 1900 / 0.7
680	6 / 152.4 x 80 / 2032	500 / 1900 / 0.7

Code-Filter O-Ring ◆	Material
H13 (Standard for glass fiber and aramid fiber filters)	Nitrile
H13U ³	Nitrile U-Cup
J (Standard for polypropylene filters)	Ethylene Propylene
JU ³	Ethylene Propylene U-Cup
H4	Silicone
H	Fluoroelastomer

3) U-Cup seal is standard for the 1 micron composite filter.

Filter Cartridge Pressure Drop (typical) per Filter Length Shown⁴

Medium Type	Grade ●	Absolute Liquid Removal Rating (microns) at 99.98% by particle count ⁵	508 mm / 20 inch length		1016 mm / 40 inch length		1524 mm / 60 inch length		2032 mm / 80 inch length	
			psid/100gpm	mbar/M ³ /hr	psid/100gpm	mbar/M ³ /hr	psid/100gpm	mbar/M ³ /hr	psid/100gpm	mbar/M ³ /hr
HDC II Medium	J060	6	0.158	0.48	0.080	0.24	0.058	0.17	0.040	0.12
	J100	10	0.120	0.36	0.060	0.18	0.040	0.12	0.030	0.09
	J200	20	0.100	0.30	0.050	0.15	0.033	0.10	0.025	0.08
Profile Medium in Ultipleat Format	UY020 ⁶	2	1.091	3.31	0.540	1.64	0.362	1.10	0.270	0.82
	UY045	4.5	0.489	1.48	0.242	0.73	0.162	0.49	0.121	0.37
	UY060	6	0.395	1.20	0.196	0.59	0.131	0.40	0.098	0.30
	UY100	10	0.344	1.04	0.170	0.52	0.114	0.35	0.085	0.26
	UY200	20	0.243	0.74	0.120	0.36	0.080	0.24	0.060	0.18
	UY400 ⁷	40	0.182	0.55	0.090	0.27	0.060	0.18	0.045	0.14
	UY700 ⁷	70	0.040	0.12	0.020	0.06	0.013	0.04	0.010	0.03
UY1000 ⁷	90	0.027	0.08	0.013	0.04	0.009	0.03	0.007	0.02	
Ultipor GF Medium	GF020	2	0.219	0.66	0.110	0.33	0.073	0.22	0.055	0.17
	GF060	6	0.180	0.55	0.090	0.27	0.060	0.18	0.045	0.14
	GF100	10	0.159	0.48	0.080	0.24	0.053	0.16	0.040	0.12
	GF200	20	0.119	0.36	0.060	0.18	0.040	0.12	0.030	0.09
	GF400 ⁷	29	0.100	0.30	0.050	0.15	0.033	0.10	0.025	0.08
Ultipleat CAS Medium	CAS010	1	1.496	4.54	0.740	2.25	0.496	1.51	0.370	1.12

4) Multiply this value by the total system flow to determine the aqueous pressure drop. For fluids other than water, multiply this value by the fluid's viscosity at the operating temperature in centipoise. This value is the pressure drop across the Ultipleat High Flow filter(s) only; it must be added to the pressure drop contribution from the Ultipleat High Flow filter housing.

5) The test procedure used is an adaptation of ISO 4572, modified to determine the micron size above which particles are quantitatively removed.

6) 2 micron at 99% efficiency.

7) Precision evaluation of the 99.98% removal efficiency for these coarse grades is not possible with the ISO modified test procedure utilized. The removal efficiency was determined by the maximum spherical particle analysis.



Pall Corporation

25 Harbor Park Drive
Port Washington, NY 11050
+1 516 484 3600 telephone
+1 800 289 7255 toll free US

Portsmouth-UK
+44 (0)23 9230 3303 telephone
+44 (0)23 9230 2507 fax

Filtration. Separation. Solution.SM



Visit us on the Web at www.pall.com

Pall Corporation has offices and plants throughout the world. For Pall representatives in your area, please go to www.pall.com/contact

Because of technological developments related to the products, systems, and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit www.pall.com to verify that this information remains valid. Products in this document may be covered by one or more patent numbers. For a complete list of Pall's patents please visit www.pall.com/main/about-pall/patents.page.

© Copyright 1999, 2015 Pall Corporation. Pall, , Ultipleat, HDC, Ultipor, and Profile are trademarks of Pall Corporation.

® Indicates a Pall trademark registered in the USA. **Filtration. Separation. Solution.SM** and **BETTER LIVES. BETTER PLANET.** are service marks of Pall Corporation.

PIUHFEN8

Produced in the USA

November 2015