

## **DECLARATION OF COMPLIANCE**

### **Pall Aria™ Filter Modules**

**“W” Code**

#### **Module Part Numbers:**

#### **PFBUNA-620C**

The Pall Aria filter modules are designed for contact with aqueous foodstuffs. These modules can be used with water in filtration flow conditions, following flushing.

An initial flush is recommended prior to use.

Issued	20 June 2012
Revised	24 April 2025
Expires	28 February 2027
Reference	FBDCUNACENj
Page	1 of 2



Syed Sirajuddin  
Pall Sàrl and MEA QARA Manager

#### **Components**

Membrane	PVDF
Housing	Acrylonitrile-Butadiene-Styrene
Potting and Cross-plate	Polyurethane resin ('C' type)
Sleeve	Polypropylene
O-ring Seal	Ethylene Propylene Copolymer

The modules are packaged with the following solution: Calcium chloride 30 wt% and Water 70 wt%.  
The modules must be flushed prior to use to remove this solution.

#### **Declaration**

Pall Aria filter PFBUNA-620C modules comprise of materials that meet regulatory and legislative requirements and guidelines for food contact in that:

#### **Europe**

The "W" Code Pall Aria filter modules, PFBUNA-620C, meet the requirements for food contact as detailed in European Regulation (EC) Numbers 1935/2004 and 10/2011 in that:

The product has been assessed by the manufacturer, in conjunction with a consulting and Testing Service, under the Plastics Materials and Articles in Contact with Foodstuffs Regulations laid out in European Regulation (EU) number 10/2011. All substances identified as being used in the manufacture of the above products were (a) listed in the above legislation either with or without restrictions, or (b) not subject to the provisions of the above legislation.

The supplier certifies that the materials of construction are not subject to the provisions of EC Regulation 1895(2005) and/or do not use BADGE, BFDGE or NOGE.

Tests have shown that the PFBUNA-620C module will meet all applicable Specific Migration Limits and Overall Migration Limits in 20 % ethanol and 3 % acetic acid when tested under conditions of repeat usage at 40 °C (104 °F) provided that the flow rate through the filter is greater than the minimum recommended flow rate of 50 L per hour.

Users should satisfy themselves that these materials are suitable for use in their specific food application.

Note:



## WARNING:

This product can expose you to chemicals including BPA, DBP and DEHP which are known in the State of California to cause birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### Process Quality System

Manufactured in Japan and Supplied by Pall Sàrl. Made in Japan.  
This product is manufactured under a Quality Management System certified to ISO 9001:2015.

### Supplied in Europe by

Pall Sàrl  
Av. De Tivoli  
1700 Fribourg  
Switzerland  
CH-1700



PALL CORPORATION

+1-866-905-7255 **Food and Beverage toll free**  
[foodandbeverage@pall.com](mailto:foodandbeverage@pall.com)

#### Corporate Headquarters

Port Washington, NY, USA  
+1-800-717-7255 toll free (USA)  
+1-516-484-5400 phone

#### European Headquarters

Fribourg, Switzerland  
+41 (0)26 350 53 00 phone

#### Asia-Pacific Headquarters


Singapore  
+65 6389 6500 phone

Visit us on the Web at [www.pall.com/foodandbev](http://www.pall.com/foodandbev)

Pall Corporation has offices and plants throughout the world. To locate the Pall office or distributor nearest you, visit [www.pall.com/contact](http://www.pall.com/contact).

The information provided in this literature was reviewed for accuracy at the time of publication. Product data may be subject to change without notice. For current information consult your local Pall distributor or contact Pall directly.

*IF APPLICABLE* Please contact Pall Corporation to verify that the product conforms to your national legislation and/or regional regulatory requirements for water and food contact use.

© Copyright 2025, Pall Corporation. Pall,  and Aria are trademarks of Pall Corporation. ® Indicates a trademark registered in the USA.  
FBDCUNACENj  
APRIL 2025