

Nexis® A Filter Cartridges

For Clarification and Particle Removal

Nexis A filter cartridges are high performance melt blown depth filters ideal for use in rigorous food and beverage clarification and particle removal applications.

Description

Nexis A series high efficiency depth filter cartridges are constructed using an advanced, microprocessor-controlled CoLD Melt™ production process that permits the creation of multiple filtration zones within a single filter cartridge. The multi-zone design produces a gradient pore structure which effectively captures larger particles in the outer sections of the filter cartridge while providing highly efficient and consistent removal of smaller particles in the inner sections.

Interlocking and thermally bonded large diameter support fibers combined with ultra-thin filtration fibers create a rigid filter matrix that withstands dynamic operating conditions. A high internal void volume enables the capture of more contaminant than conventional melt-blown, string wound or molded filter cartridges.

The result is a high performance, low cost of ownership cartridge characterized by robustness in operation, long service life, and excellent removal efficiency.

Features	Benefits
Fixed fiber matrix with interlocking, thermally bonded support and filtration fibers	<ul style="list-style-type: none"> • Excellent removal efficiency • Consistent filtration performance • No unloading of contaminants
Micro-thin fibers with continuous graded pore structure provide pre- and fine filtration in the same cartridge	<ul style="list-style-type: none"> • High void volume for high dirt holding capacity and long service life • Economical cost per filtered volume • Lower disposal costs
Proprietary high strength center core	<ul style="list-style-type: none"> • Reliable even under high differential pressure conditions
All polypropylene construction without adhesives, binders, resins or silicone	<ul style="list-style-type: none"> • Broad chemical compatibility, suitable for use in a variety of fluids



Nexis A Filter Cartridges

Materials of Construction

Component	Description
Filter Medium	Polypropylene
Core, Fin End and End Cap	Polypropylene
SOE Style Cartridges only	
Adaptor	Polypropylene
O-Ring Seal	Silicone Elastomer Ethylene Propylene Rubber

Quality

- Cartridges produced in a controlled environment
- Manufactured within a Quality Management System certified to ISO 9001:2008

Food Contact Compliance

Please refer to the Pall website www.pall.com/foodandbev for a Declaration of Compliance to specific National Legislation and/or Regional Regulatory requirements for food contact use.

Technical Information


Operating Characteristics in Compatible Fluids¹

Maximum Differential Pressure ²	Operating Temperature
1.03 bard (15 psid)	82 °C (180 °F)
1.72 bard (25 psid)	66 °C (150 °F)
4.14 bard (60 psid)	30 °C (86 °F)

¹ Fluids which do not swell, soften or adversely affect any of the filter components


² Recommended change-out differential pressure is 2.4 bard (35 psid), provided the maximum differential pressure (based on temperature) is not exceeded.

Flow Rates³



³ Typical initial clean Δp for a 254 mm (10 inch) cartridge, clean water at 20 °C (68 °F). For liquids with viscosity greater than 1 cp, multiply the Δp by the viscosity.

Figure 1: Cutaway view of a Nexis filter, illustrating unique, proprietary CoLD Melt fiber technology for highly efficient contaminant removal, longer service life, and improved strength



Sterilization and Sanitization

- Single open end (SOE) cartridges may be autoclaved for 30 minutes at 121 °C (250 °F) under no end load conditions. Cartridges should be cooled to system operating temperatures prior to use.
- *In situ* steam sterilization is not recommended.

Ordering Information

This information is a guide to the part numbering structure and possible options. For availability of specific options please contact Pall. Refer to Pall for housing details.

Part Number: **NXA**   **U**  **W**  **480**

Example Part Number: **NXA1030UM7WS480**

See bold reference codes in tables.

Table 1: Removal Rating⁴

Code	Description
5	5 µm
10	10 µm
20	20 µm
30	30 µm

⁴ Nexis A filters provide a removal efficiency of >99.9% at the stated rating in compatible fluids. Particulate removal rating is determined by a single pass test based on ASTM F-795 (see Pall Technical Bulletin 1903-^{*}T, latest revision).

Table 2: Length

Code	Description
DOE Style only:	
10	254 mm (10")
20	508 mm (20")
295	749 mm (29.5")
30	762 mm (30")
SOE Style only:	
10	254 mm (10")
20	508 mm (20")
30	762 mm (30")
40	1016 mm (40")

Table 3: Adaptor

Code	Description
blank	DOE with no endcaps
M3	SOE - single open end with flat closed end and external 222 O-rings
M7	SOE - single open end with fin end, 2 locking tabs and external 226 O-rings
M8	SOE - single open end with fin end and external 222 O-rings

Table 4: O-ring Seal Material⁵

Code	Description
S	Silicone Elastomer
E	Ethylene Propylene Rubber

⁵ For M3, M7 and M8 styles only



Pall Food and Beverage

25 Harbor Park Drive
Port Washington, NY 11050
+1 516 484 3600 telephone
+1 866 905 7255 toll free US

Visit us on the Web at www.pall.com/foodandbev

Pall Corporation has offices and plants throughout the world. For Pall representatives in your area, please go to www.pall.com/contact

Please contact Pall Corporation to verify that the product conforms to your national legislation and/or regional regulatory requirements for water and food contact use.

Because of technological developments related to the products, systems, and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit www.pall.com to verify that this information remains valid. Products in this document may be covered by one or more of the following patent numbers: EP 0 830 191; US 5,591,335; US 5,653,833; US 5,681,469; US 5,690,782; US 5,730,820; US 5,733,581; US 5,741,395; US 5,783,011.

© Copyright 2014, Pall Corporation. Pall,  CoLD Melt and Nexis are trademarks of Pall Corporation. ® Indicates a trademark registered in the USA. *Filtration. Separation. Solution.* is a service mark of Pall Corporation.