

Coralon Filters

NEW: Coralon™ Filter Elements Upgrade filter elements for Ultipor[®] filters

Keeping fluids cleaner, longer, for greater value

Coralon filters represent a significant advancement in equipment protection and are a direct replacement (same form, fit, and function including fluid and temperature compatibility) for current Ultipor filter elements.

Features

- Direct replacement for Ultipor elements
- Advanced pack design
- Stress-resistant media technology
- Out-to-in flow path*
- * except for in-tank filter options

Innovative Media Performance

Pall's new series of hydraulic & lube filter elements feature SRT (stress-resistant technology) media for unsurpassed performance and value. Coralon elements provide:

- Low element pressure drop for small envelope size and long life
- Optimum performance under system stresses at all stages of filter life for consistently cleaner fluid

In addition to improved performance, what differences will I see?

- Coralon filters upgrade Pall Ultipor III, Ultipor III Coreless, Ultipor Dirt Fuse, Ultipor SRT, Ultipor Plus, Ultipor Max, and Red1000 elements in all standard medium grades (Z, P, N, S, T).
- The new elements will have a medium code of "C" in place of existing "U", "D", "K" "M" or "X" code in the current filter element part number; see examples in the adjacent table.

Examples of new filter element part number

Existing number	New number
HC9600FKP8Z	HC9600FCP8Z
HC9601FDP13Z	HC9601FCP13Z

The part number is printed on the bottom endcap of the filter element





Coralon Filter Elements

Specifications

Element Collapse Pressure Rating:

10 bard (150 psid) minimum for Coreless Ultipor filter elements (polymer end caps) and for use in filters with bypass 20 bard (300 psid) minimum for Ultipor filter elements (metal end caps and core) and for use in filters with bypass

210 bard (3,045 psid) minimum for Ultipor high strength filter elements (metal end caps and core) and for use in filters without bypass

Temperature Range		
Fluorocarbon:	-29°C (-20°F) to +120°C (+250°F)	
Nitrile:	-43°C (-45°F) to +120°C (+250°F)	
Note :	Maximum 60°C (140°F) in water	
	based fluids	
Seals:	Fluorocarbon or nitrile	
Fluid Compatibility:	Compatible with petroleum oils,	
	water glycols, water-oil emulsions,	
	and high water containing fluids.	
Filter Construction:	Cored filter elements - Corrosion	
	protected end caps and core	
	Coreless filter elements - Polymer	
	end caps only	
Filter Element medium:	Inorganic fibers impregnated and	
	bonded with epoxy resins.	
All Concluse filter alexandra and rear fact word by Dellite and the		

All Coralon filter elements are manufactured by Pall to exacting procedures and strict quality controls. Elements are validated to the following ISO test protocols :

- Filter Ratings:
 - Cyclic Stabilization Test (80% Δp) based on SAE ARP4205. For ISO Code ratings, see Table 1
 - $\beta_{X(C)} \ge 1000$ multi-pass filter ratings (per ISO 16889)
- Element Collapse Pressure Rating (ISO 2941)Fluid Compatibility (ISO 2943)
- Flow vs. Pressure Drop (ISO 3968)
- Flow Fatique (ISO 3724)
- Fabrication Integrity (ISO 2942)

For further information on test protocols and certification, please contact Pall sales.



Pall Corporation

25 Harbor Park Drive Port Washington NY 11050 +1 516 484 3600 telephone +1 800 289 7255 toll free US

Portsmouth - UK +44 (0)23 9233 8000 telephone +44 (0)23 9233 8811 fax industrialeu@pall.com

Filtration. Separation. Solution.sm

Measuring Filter Performance - the Cyclic Stabilization Test (based on SAE ARP4205):

Conditions such as varying flow, cold starts, shock and vibration can potentially reduce the effectiveness of a filter in an operating system.


The Cyclic Stabilization Test examines the effects of cyclic flow conditions and dirt loading on the capture and retention characteristics of the filter. The result is an improved filter performance reporting method that simply tells the user via ISO Codes (see Table 1) the level of contamination control that can be maintained throughout the filter's service life.

Table 1 - Filter Performance Ratings

Coralon Filter Grade	βx(c) ≥ 1000 per ISO 16889	ISO Code Rating per Stress- Resistance Test ($80\% \Delta p$)*
CZ	3	10/08/03
CP	5	12/09/07
CN	7	14/11/06
CS	12	15/11/06
CT	22	16/14/08

* based on 60 psid terminal pressure drop

The Coralon Filter Performance Advantage



A critical measure of a filter's performance is its ability to sustain fluid cleanliness throughout its service life.

This graph compares a Coralon 7μ m(c) rated filter to an Ultipor III filter and four competitors' products with equivalent ratings.

Only Coralon filters produce sustained fluid cleanliness over the full life of the filter.



Visit us on the Web at www.pall.com

Pall Corporation has offices and plants throughout the world. For Pall representatives in your area, please go to www.pall.com/contact

Because of technological developments related to the products, systems, and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit www.pall.com to verify that this information remains valid.

© Copyright 2015, Pall Corporation. Coralon, Ultipor Pall and (ALL) are trademarks of Pall Corporation. © Indicates a trademark registered in the USA. Better Lives. Better Planet and Filtration. Separation. Solution.sм are service marks of Pall Corporation.

M&ECOBENa