



Carbon Capsule

Description

Removes Odor, Colloids, and Organics from Liquids Using Activated Carbon

- ▶ Finely divided carbon provides an active surface area of 70,000 m²
- ▶ Ready to use and disposable

Application

- ▶ For laboratory and reagent-grade water and chemical filtration
- ▶ Protect laboratory from organic solvent odor



Specifications

Materials of Construction

- ▶ Filter Media: 100 g activated carbon
- ▶ Housing: Polycarbonate
- ▶ Upstream/Downstream Supports: Nylon felt pad
- ▶ Adapters: Nylon

Typical Effective Surface Area

- ▶ 70,000 m² of carbon

Dimensions

- ▶ Housing Length: 18.7 cm (7.4 in.)
- ▶ Overall Length: 25.4 cm (10 in.)
- ▶ Diameter: 5.8 cm (2.3 in.)

Inlet/Outlet Connections

- ▶ 3/8 in. FNPT; includes optional hose barb fittings to accept 12.7 mm (1/2 in.) ID tubing

Maximum Operating Temperature

- ▶ 80 °C (176 °F)

Maximum Operating Pressure

- ▶ 3.4 bar (340 kPa, 50 psi) at ambient temperature

Ordering Information

Part Number	Description	Pkg	Price	Qty
Carbon Capsule				
12011	Carbon capsule	1/pkg	NA	<input type="text" value="0"/>

Contact Information

Pall Office(s)

World Headquarters

25 Harbor Park Drive
Port Washington, NY 11050
USA
Phone: (516) 484-3600
Alternate Phone: **1-800-289-7255**
Fax: (516) 801-9754
[Driving Directions](#)
[Map](#)

Distributor(s)

VWR International

1310 Goshen Parkway
West Chester, PA 19380
USA
Phone: 800.932.5000
Phone: 610.431.1700
Fax: 610.436.1760
Web: <http://www.vwrsp.com/>

© 2014, Pall Corporation, Pall, and other names are trademarks of Pall Corporation.
® indicates a registered trademark in the USA.