

Emflon® Filter (1.5 nm)



Data Sheet MEEMFGASEND

Description

Emflon filter elements are designed for ≥ 1.5 nm filtration of bulk gas applications found in the semiconductor industry.

Features & Benefits

- Wide variety of applications
- High particle retention
- High flow rates vs. differential pressure
- Optimized cartridge design
- Manufactured in a cleanroom environment
- 100% integrity tested




Specifications

Materials of Construction

Components	Materials
Filter Medium	PTFE
Media Support	Polypropylene
Inner Core	Polypropylene
Outer Cage	Polypropylene
End Caps	Polypropylene
O-ring Options	Acid proof fluoroelastomer, FEP encapsulated fluoroelastomer
Gasket Options	NBR, PTFE, Fluoroelastomer, EPDM

Removal Ratings	≥ 1.5 nm (0.001.5 μ m)		
Filter Areas	AB1	MCY1001	MDY1002
	10" / 254 mm : 9.45 ft ² / 0.88 m ²	10" / 254 mm : 9.26 ft ² / 0.86 m ²	20" / 508 mm : 18.52 ft ² / 1.72 m ²
Nominal Length	10" / 254 mm 20" / 508 mm 30" / 762 mm 40" / 1,016 mm		20" / 508 mm 30" / 762 mm
Diameter	2.75" / 70 mm		
O-ring Size / End Caps	Code 3 (222 double O-ring / flat end) Code 8 (222 double O-ring / finned end) Code 7 (226 double O-ring bayonet lock / finned end)		
Maximum Operating Temperature	194 °F / 90 °C		
Maximum Forward Differential Pressure	80 psid @ 120 °F / 5.5 bar @ 50 °C 50 psid @ 194 °F / 3.5 bar @ 90 °C		

Pressure Drop vs. Gas Flow Rate (AB1, MCY1001)



Part Numbers / Ordering Information

O-Ring Seal

AB 1 2 3 E 4

Table 1

Code	Nominal length (mm / in)
1	254 / 10
2	508 / 20
3	762 / 30
4	1,016 / 40

Table 2

Code	Removal Ratings
FR	≥ 1.5 nm

Table 3

Code	O-ring Specifications
7	AS568A-226
8	AS568A-222
3	AS568A-222

Table 4

Code	O-ring Materials ¹
H1	FEP encapsulated fluoroelastomer
HF	Acid-proof fluoroelastomer

¹ Other O-ring material options available.

Gasket seal

MCY1001 7 E 8

MDY100 9 7 E 8

Table 7

Code	Removal Ratings
FR	≥ 1.5 nm

Table 8

Code	Gasket Materials
H13	NBR
H2	PTFE
H	Fluoroelastomer
J	EPDM

Table 9

Code	Nominal length (mm / in)
2	508 / 20
3	762 / 30

Representative example part numbers

O-Ring Seal

AB1FR3EHF	AB2FR8EHF	AB3FR7EHF	AB4FR7EHF
AB1FR3EH1	AB2FR7EHF	AB3FR8EHF	AB4FR3EHF
AB1FR7EH1	AB2FR3EHF	AB3FR3EHF	
AB1FR3EHF	AB2FR3EH1	AB3FR3EH1	
	AB2FR7EH1		

Gasket seal

MCY1001FREH2	MDY1002FREH13	MDY1003FREH13
MCY1001FREJ	MDY1002FREH2	



Microelectronics

25 Harbor Park Drive
Port Washington, NY 11050
+1 516 484 3600 telephone
+1 800 360 7255 toll free US

Nihon Pall Ltd.

6-5-1, Nishishinjuku,
Shinjuku-ku
Tokyo 163-1325 Japan
+81 3 6901 5700 telephone
+81 3 5322 2109 fax

Pall Corporation has offices and plants throughout the world. To locate the Pall office or distributor nearest you, visit www.pall.com/contact.

The information provided in this literature was reviewed for accuracy at the time of publication. Product data may be subject to change without notice. For current information consult your local Pall distributor or contact Pall directly.

IF APPLICABLE Please contact Pall Corporation to verify that the product conforms to your national legislation and/or regional regulatory requirements for water and food contact use.

© Copyright 2025, Pall Corporation. Pall, , and Emflon are trademarks of Pall Corporation.® Indicates a trademark registered in the USA.