UltiKleen[™]STL Filter



Data Sheet MESTLENb

Description

The UltiKleen STL filter is an advanced all-fluoropolymer cartridge that is ideal for filtering organic strippers. It is offered with removal ratings of 1 µm and 5 µm. Pall's proprietary media layering construction provides higher flow rates and longer service life than conventional filters. The filter's high flow rates result in rapid bath clean-up and improved bath quality. The UltiKleen STL filter is widely used in today's bulk chemical distribution systems.

Features & Benefits

- Large filter surface area is achieved through Pall's patented, crescentshaped, Ultipleat[®] filter design
- Extended filter service life makes for a very cost-effective product
- Very high flow rates
- Excellent compatibility
- Rapid bath clean-up
- Suitable for wide a range of chemical filtration applications




Specifications

Materials of Construction


| Components | | Materials |
|-------------------------------|---------------------|--|
| Filter Medium | | PTFE |
| Support and Drainage | | Fluorocarbon |
| Core, Cage and End Caps | | PFA |
| O-ring | | FEP encapsulated fluoroelastomer |
| Removal Rating | | 1 μm, 5 μm |
| Filter Area | | 1.1 m² / 11.8 ft² |
| Configurations | Nominal Length | 254 mm / 10" |
| | Nominal Diameter | 70 mm / 2.75" |
| Maximum Operating Temperature | | 110 °C / 230 °F |
| Maximum Differential Pressure | Forward | 0.59 MPa @ 50 °C / 86 psid @ 122 °F 0.41 MPa @ 110 °C / 59 psid @ 230 °F |
| | Reverse (momentary) | 0.34 MPa @ 20 °C / 49 psid @ 68 °F |

Please contact your Pall representative for information on housings.

Typical Flow Characteristics - 1cP fluid, 20 °C



Dimensions (Nominal)



Part Numbers / Ordering Information

| Part Number | Removal Rating (µm) | O-Ring Material |
|------------------|---------------------|----------------------------------|
| MRF1UFNS25H1-STL | 1 | FEP encapsulated fluoroelastomer |
| MRF1UFCS25H1-STL | 5 | FEP encapsulated fluoroelastomer |



Microelectronics

25 Harbor Park Drive Port Washington, NY 11050 +1 516 484 3600 telephone +1 800 360 7255 toll free US

Nihon Pall Ltd.

6-5-1, Nishishinjuku, Shinjuku-ku Tokyo 163-1325 Japan +81 3 6901 5700 telephone +81 3 5322 2109 fax Pall Corporation has offices and plants throughout the world. To locate the Pall office or distributor nearest you, visit www.pall.com/contact.

The information provided in this literature was reviewed for accuracy at the time of publication. Product data may be subject to change without notice. For current information consult your local Pall distributor or contact Pall directly.

IF APPLICABLE Please contact Pall Corporation to verify that the product conforms to your national legislation and/or regional regulatory requirements for water and food contact use.

© Copyright 2025, Pall Corporation. Pall, (ALL), and Ultikleen and Ultipleat are trademarks of Pall Corporation. ® Indicates a trademark registered in the USA.

