

Ultramet-L[®] 4000 Series Filter Assembly (1.5 nm)




Data Sheet MEUL40ENa

Description

The Ultramet-L[®] 4000 Series Filter Assembly is a unique, all 316L stainless steel filter designed for ≥ 1.5 nanometer ($0.0015 \mu\text{m}$) filtration of semiconductor process gases.

Features & Benefits

- All 316L stainless steel construction
- State-of-the-art 316L stainless steel media
- Excellent particle removal efficiency vs. pressure drop
- Accommodates extremely high flow rates for the assembly size
- Excellent gas displacement and desorption characteristics
- High temperature and pressure capabilities
- Compact size for ease of installation
- Wide variety of fitting options available
- 100% helium leak tested
- Cleanroom manufactured and packaged




Specifications

Filter Medium	316L stainless steel
Internal Surface Finish	$\leq 7 \mu\text{in} / 0.18 \mu\text{m R}_a$
Housing	Electropolished 316L stainless steel Housing material meets or exceeds VIM / VAR specifications
Removal Rating	$\geq 1.5 \text{ nm}$
Particle Removal Characteristics	10^9 particle reduction up to 6 slpm / 0.2 scfm 10^4 particle reduction up to 75 slpm / 2.6 scfm
Connections	$\frac{1}{4}$ ", $\frac{1}{2}$ " Gasket Seal, Male / Male (VCR ¹ or compatible) $\frac{1}{4}$ " Compression Seal, Male / Male (Swagelok ¹ or compatible) $\frac{1}{4}$ " Butt Weld (0.035" / 0.89 mm wall)


Leak Rating	100% helium leak tested to $10^{-9} \text{ atm}\cdot\text{cc/s}$ Design validated to $10^{-11} \text{ atm}\cdot\text{cm}^3/\text{s}$
Maximum Operating Pressure	207 bar @ 38 °C / 3000 psig @ 100 °F 116 bar @ 450 °C / 1685 psig @ 840 °F
Maximum Allowable Differential Pressure	8.6 bar @ 38 °C / 125 psid @ 100 °F 4.1 bar @ 450 °C / 60 psid @ 840 °F
EU Pressure Equipment Directive	Assemblies have been evaluated and designed using SEP per the European Union's Pressure Equipment Directive 2014/68/EU and are not CE marked.

¹ VCR and Swagelok are trademarks of Swagelok Co.

Pressure Drop vs. Gas Flow Rate



Dimensions



Part Numbers / Ordering Information

Part Number	Description	Length (L) (in / mm)
GLFF4000VM4	¼" Gasket Seal (VCR or Compatible) Male / Male	3.31 / 84 (L ₁)
GLFF4000SM4	¼" Compression Seal (Swagelok or Compatible) Male / Male	2.88 / 73 (L ₁)
GLFF4000BW4	¼" Butt Weld, 0.035" / 0.89 mm wall	1.75 / 45 (L ₂)
GLFF4000VMM8	½" Gasket Seal (VCR or Compatible) Male / Male	3.35 / 85 (L ₁)

Unit conversion: 1 bar = 100 kilopascals



Microelectronics

25 Harbor Park Drive
Port Washington, NY 11050
+1 516 484 3600 telephone
+1 800 360 7255 toll free US

Nihon Pall Ltd.

6-5-1, Nishishinjuku,
Shinjuku-ku
Tokyo 163-1325 Japan
+81 3 6901 5700 telephone
+81 3 5322 2109 fax

Pall Corporation has offices and plants throughout the world. To locate the Pall office or distributor nearest you, visit www.pall.com/contact.

The information provided in this literature was reviewed for accuracy at the time of publication. Product data may be subject to change without notice. For current information consult your local Pall distributor or contact Pall directly.

IF APPLICABLE Please contact Pall Corporation to verify that the product conforms to your national legislation and/or regional regulatory requirements for water and food contact use.

© Copyright 2025, Pall Corporation. Pall, , and Ultramet-L are trademarks of Pall Corporation.® Indicates a trademark registered in the USA.